


### INLET VALVE

DN	C [mm]	D [mm]	E [mm]	F [mm]	Ship Wt. [Kg]
8"	63	520	152	280	27
10"	63	540	152	280	34
12"	76	600	200	400	68
16"	100	680	200	510	136
18"	110	720	200	510	152
20"	152	750	200	510	192

### STANDARD FEATURES

- Heavy-duty design;
- 60° cone;
- Smooth interior;
- Manway or handmay;
- Butterfly valve with pneumatic actuator;
- Rotatable outlet;
- Erosion allowances on wear surface;
- Aeration jets.

### OPTIONAL FEATURES

- Interior coatings;
- Multiple inlets;
- Stainless construction AISI 304/316;
- Higher pressure and temperature ratings;
- ATEX design 94/9/CE; 
- Electronic multi pressure control.

### SPECIFICATIONS

- Design pressure: 6 bar;
- Temperature range: -10 °C a +50 °C;
- PED 97/23/CE.

### TRANSPORTER

Model No.	Capacity [Lt]	A [mm]	Dia.[mm]	Ship Wt. [Kg]
42-60-10	280	2060	1066	635
42-60-20	600	2360	1066	700
48-60-30	850	2666	1220	816
48-60-40	1100	3124	1220	975
48-60-50	1400	3430	1220	1100
54-60-60	1700	3500	1372	1270
54-60-70	2000	3810	1372	1360
60-60-90	2500	4114	1524	1565
60-60-100	2800	4267	1524	1680
72-60-150	4200	4650	1830	2180
84-60-200	5600	4724	2133	2500
96-60-250	7000	4800	2440	3040
96-60-300	8500	5333	2440	3356

THE **NOL-TEC** BLENDER TRANSPORTERS ARE DESIGNED TO PROVIDE TROUBLE-FREE BLENDING AND DENSE PHASE PNEUMATIC CONVEYING OF MOST MATERIALS.