


STANDARD FEATURES

- Vessel capacity: 25 litres
- Butterfly inlet valve DN 150
- Wear-resistant pipe outlet
- Pre-assembled air and electrical controls
- Suitable for indoor or outdoor service
- PED Certified (Pressure Equipment Directive) 97/23/EC
- Electrical: 24 VCC
- Pipe outlet: DN50

SPECIFICATIONS

- PED certified vessel: 6 Bar
- Working pressure 2 Bar (*)
- Temperature range : -10° C. to 120° C.
- Air:
 - filtered (5 mm, class 3 table 3.1A ISO 8573.1)
 - residual oil 0,01mg/m³ / 1mg/m³ (class 3 table 3.1C ISO 8573.1)
 - dry, compressed air from 5 bar to 6 bar (dew point -40°C / 3°C, class 2 - table 3.1B ISO 8573)
- Air consumption from 60 to 170 m³/h (*)
- (*) Depending on: product, distance, capacity, ect to define in phase of engineering preliminary

OPTIONAL FEATURES

- Several vessel capacities
- Stainless product contact AISI 304 e AISI 316
- Control package
- Control for convey line with Air Assist
- Maximum temperature design: 200° C
- Electrical: 24 Vdc-110/120 Vac,50-60 HZ
- Outlet DN65, DN80 plain and flanged end.
- Esecution up to 400°C with Double Ceramic Disc Valve
- ATEX 94/9/CE design 

MODEL	A	B	C	WEIGHT (Kg)
12	372	690	485	100
18	380	769	485	120
25	380	818	485	160
60	400	1090	485	200
100	274	1013	780	400

THE **NOL-TEC** MINI-JET™ TRANSPORTER IS SUITABLE TO CONVEY SEVERAL POWDERIZED PRODUCTS.

TECHNICAL FEATURES:

- PRESSURE DENSE PHASE CONVEYING
- CAPACITY UP TO 5m³/h
- DISTANCES UP TO 150m.

THE **NOL-TEC** MINI-JET™ IS DESIGNED WITH LOW MAINTENANCE COMPONENTS.

THE UNIT IS SUITED FOR INSTALLATION ON THE BOTTOM OF SILOS, OR DUST COLLECTOR HOPPERS. THE UNIT COULD BE ISOLATED WITH A VALVE AND DIRECTLY CONNECTED WITH THE HOPPER FLANGE.