


BENDS 90°

BEND	DN	R [mm]	Ød [mm]	ØD [mm]	L [mm]	WEIGHT [Kg]
2"	50	750	53	60	305	72
3"	80	750	78	89	305	93
3"	80	1000	78	89	305	116
4"	100	750	102	114	305	90
4"	100	1000	102	114	305	113
4"	100	1220	102	114	305	128
5"	125	1000	128	141	305	168
5"	125	1220	128	141	305	192
6"	150	1220	153	168	305	201
6"	150	1500	153	168	305	238
8"	200	1220	203	219	305	235
8"	200	1500	203	219	305	277

COMPRESSION COUPLING VICTAULIC STYLE 99



STANDARD FEATURES

- Wear-resistant basalt
- 8 Hardness Mohs scale
- Thickness of basalt 20 mm
- Thickness of mild steel lining 3 mm
- Paint primer and top coat RAL 7035
- Conform to UNI EN 1092-1 (equivalent to ASME B16.5)

OPTIONAL FEATURES

- Angle 15 °, 30 °, 45 °, 60 °, 90 °
- Possibility to run custom diameter, radius and length

BENDS AND PIPES SUITABLE FOR CONVEYING OF GRANULAR MATERIALS AND ABRASIVE POWDERS, ABLE TO REDUCE DRASTICALLY WEARING, INCREASING PLANT PRODUCTION TIME. LIFE TIME OF EACH SINGLE BEND DEPENDS BY LINING MATERIAL AND APPLICATIONS.

ALSO SUITABLE FOR FOOD APPLICATIONS.