


STANDARD FEATURES

- Mild steel construction;
- Special fluidization membrane (OMNI);
- Pressure design 6 bar;
- Working pressure up to 6 bar;
- Inlet valve;
- Flanged outlet;
- PED 97/23/EC;
- Wear resistant design .

OPTIONAL FEATURES

- Inlet rotating disk valve;
- 115 Vac/24 Vdc/230 Vac electrical supply;
- 230 Vac 50/60 Hz control panel supply;
- Stainless steel construction 304/316;
- Tailor made internal surface treatment (teflon coated);
- Inflatable seat inlet butterfly valve ;
- ATEX design 94/9/CE; 
- Maximum working temperature up to 400 °C.

SPECIFICATION

- Air:
 - Clean and dry at correct pressure dew point;
 - 6 bar minimum.
- Working temperature: -30 ÷ 425 °C.
- Air consumption: 100 to 350 m³/h.

Model No.	A	B	C
25 L	DN150	DN80	1100
60 L	DN150	DN80	1297

THE **NOL-TEC** MINIJET F.A.™ TRANSPORTER IS SUITED FOR FLY ASH DENSE PHASE CONVEYING SYSTEM AND COMPOSED BY COMPONENTS THAT REQUIRE LOW MAINTENANCE.

IT CAN BE INSTALLED UNDER A SILO, BAG HOUSE HOPPER, ESP HOPPER, A BULK BAG UNLOADING STATION, ETC.

THIS UNIT CAN BE ISOLATED FROM A VALVE AND DIRECTLY FLANGED UNDER THE SURGE HOPPER.

A SPECIAL ROTATING DISK VALVE IS SUITED FOR HEAVY DUTY, HIGH TEMPERATURE AND HIGH PRESSURE SERVICE WITH REDUCED MAINTENANCE.