



HIGH PRESSURE MODEL NO.	LOW PRESSURE MODEL NO.	FILTER AREA (m ²)	A	B	C	D	m ³ / h a 7 bar	Ship Wt. (Kg)
18-HPRD-9	18-LPRD-9	2	1220	760	810	28	6.8	140
36-HPRD-9	36-LPRD-9	4	1680	760	810	28	7	170
60-HPRD-9	60-LPRD-9	6	2140	760	810	28	7.6	180
84-HPRD-9	84-LPRD-9	9	2740	760	810	28	8.5	230
60-HPRD-14	60-LPRD-14	10	2140	914	970	32	9	230
84-HPRD-14	84-LPRD-14	14	2740	914	970	32	9.8	270
60-HPRD-18	60-LPRD-18	13	2140	1070	1120	40	10	270
84-HPRD-18	84-LPRD-18	18	2740	1070	1120	40	11	310
60-HPRD-24	60-LPRD-24	17	2140	1220	1270	44	11.4	310
84-HPRD-24	84-LPRD-24	25	2740	1220	1270	44	12	350
60-HPRD-32	60-LPRD-32	25	2140	1370	1420	52	12.7	340
84-HPRD-32	84-LPRD-32	31	2740	1370	1420	52	13	400
60-HPRD-38	60-LPRD-38	28	2140	1520	1570	56	13.5	390
84-HPRD-38	84-LPRD-38	37	2740	1520	1570	56	14	440
60-HPRD-46	60-LPRD-46	32	2140	1680	1730	62	15	420
84-HPRD-46	84-LPRD-46	45	2740	1680	1730	62	16	500
60-HPRD-54	60-LPRD-54	38	2140	1830	1900	68	18	460
84-HPRD-54	84-LPRD-54	53	2740	1830	1900	68	18.7	540

STANDARD FEATURES

- Venturi, reverse jet cleaning;
- Quick release filter clamps;
- Solid state electronic timer;
- Large access door;
- Reinforced Housing
- Heavy gauge, continuous welded construction;
- Continuous cleaning;
- Bottom grid;
- Magnehelic gauge;
- Bird screen and Weatherood

OPTIONAL FEATURES

- Bag style filters;
- Variety of filter media materials;
- Exhauster
- Second access door;
- Cone aeration;
- Stainless construction AISI 304/316;
- Hopper Bottom
- High temperature design;

SPECIFICATIONS

- Air:
 - Clean and dry at correct pressure dew point;
 - 5,5 bar minimum.
- Electrical: 110-120 V, 50/60 Hz
- Temperature:
 - Timer: 4 °C to 65 °C;
 - Polyester Bags: 132 °C;
 - Polyester Cartridge and Urethane Ends: 93°C.

THE **NOL-TEC** ROUND BIN VENT/ DUST COLLECTOR IS AN EFFECTIVE METHOD OF FILTERING DUST LADEN AIR GENERATED BY ANY PROCESS OR PNEUMATIC CONVEYING SYSTEM WHERE HIGHER PRESSURES ARE REQUIRED.